CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING & INVESTIGATIONS DIVISION
BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No.:	8110-2321:0500
CATEGORY:	8110 - DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
LISTEE:	MoistureShield 801 Jefferson St, Springdale, AR, 72764 Contact: Reed, Randall (514) 351-2121 Email: randall.reed@barretteoutdoorliving.com
DESIGN:	MoistureShield Vision® Composite Deck Board, material in sizes 1" x 5.4" and *1.4" x 5.4". Installed on nominal 2" x 6" Douglas-fir joists, 16" O.C. Maximum 1/8" edge-to-edge gap spacing for 1" x 5.4". *Maximum 3/16" edge-to-edge gap spacing for 1.4" x 5.4". Refer to manufacturer's installation instructions and product data sheets.
RATING:	SFM 12-7A-4A
INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction.
MARKING:	Listee's name, model number, rating, and SFM label.
APPROVAL:	Listed as decking material for use in the Wildland Urban Interface areas when attached exterior wall covering is also composed of noncombustible or ignition-resistant material. Refer to listee's Installation Instruction Manual for details.
NOTES:	Test Protocol SFM 12-7A-4A

*Revision 12-29-21 VWW

This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: 05/31/2026

Listing Expires: 06/30/2027

Authorized By: **Michael Huang**, Program Coordinator
Fire Engineering & Investigations Division